

# Metal belt saws

## OPTI S 100 G

Light-weight and handy.

Ideal for universal use on building sites, on assembly, in the shop, in the do-it-yourself room and in agriculture

### Convincing arguments: quality, efficiency and price

- Automatic limit stop
- Automatic lowering of the saw arch using the three-point adjustment of saw arch pressure
- Ball-bearing saw belt guidance
- Ideal for use on building sites
- Quick-action vice
- Space-saving due to mitre adjustment over the saw bow



### Optional accessories:

- Substructure
- Collapsible
- Stable
- Space-saving
- Easily movable

Accessories	Item No.	€ (VAT excl.)
■ Substructure	335 1490	<b>69.00</b>
■ Bimetallic saw belt (10-14 TPI)	335 1110	<b>16.90</b>

### Convincing arguments...



- Quick-action vice for quick workpiece clamping



- Three-point adjustment of the saw arch pressure
- Automatic lowering of the saw arch



- Lockable saw arch for transport



- User-friendly safety switch according to IP 54 with undervoltage release, emergency-stop button

### Extent of supply:

- Bimetallic saw belt (10-14 TPI)
- Material limit stop
- Operating tools in a suitable holder

Model	OPTI S 100 G
Item No.	330 0100
€ (VAT excl.)	<b>499.00</b>

Technical data	
Cutting range at 0° <input type="radio"/>	100 mm
Cutting range at 0° <input type="checkbox"/>	100 x 150 mm
Cutting range at 45° <input type="radio"/>	65 mm
Cutting range at 45° <input type="checkbox"/>	100 x 60 mm
Saw belt speed	45 m/min
Saw belt dimensions	1,470 x 13 x 0.65 mm
Motor power 230 V / 50 Hz	370 W
Dimensions (L x W x H)	724 x 381 x 458 mm
Net weight	23 kg